

ACRYLIC COAT 2:1 HS PROFESSIONAL

SECTION 1: SUBSTANCE/MIXTURE IDENTIFICATION AND MANUFACTURER/SUPPLIER IDENTIFICATION

1.1. Product identification

ACRYLIC COAT 2:1 HS PROFESSIONAL
UFI 0U50-C0VU-W000-TECW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Acrylic coat (component A) to be applied with a spray gun. For professional use in car refinish.

1.3. Data of the safety data sheet supplier

Przedsiębiorstwo RANAL Sp. z o.o.
Ul. Łódzka 3
42-240 Rudniki k. Częstochowy, PL

Tel.: +48 34 329 45 03
Fax: +48 34 320 12 16
Registration number 000029202

Person responsible for the safety data sheet: ranal@ranal.pl

1.4. Emergency telephone

+48 34 329 45 03 (8.00 - 15.00)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

The mixture was classified as hazardous according to the regulations in force - see section 15 of the Safety Data Sheet.

Classification 1272/2008/EC:

Causes skin irritation (Skin Irrit. 2).

May cause drowsiness or dizziness (STOT SE 3).

Flammable liquid and vapour (Flam. Liq. 3).

2.2. Label elements

Contains: Xylene.

Pictograms:



Signal word: **Warning.**

Risk index:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

Safety index:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Do not breathe vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

2.3. Other hazards

Does not contain PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with Annex XIII of REACH.*

The mixture does not contain any substance(s) included in the list established in accordance with Art. 59 sec. 1 of the REACH Regulation due to endocrine disrupting properties or is not identified as endocrine disrupting in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in a concentration equal to or greater than 0,1 % by weight.*

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable.

3.2. Mixtures

Substance name
Concentration [% weight]
Identification numbers
Classification and labelling

Butyl acetate

the substance has an occupational exposure limit(s) (PL); substance with a Community-wide occupational exposure limit value **
15-30%

ACRYLIC COAT 2:1 HS PROFESSIONAL

EC: 204-658-1
CAS: 123-86-4
Index no: 607-025-00-1
Registration no: 01-2119485493-29-XXXX
Classification 1272/2008/EC: Flam. Liq. 3; H226; STOT SE 3; H336.

Xylene
the substance has an occupational exposure limit(s) (PL); substance with a Community-wide occupational exposure limit value *
(Note C)*
5-10% *
EC: 215-535-7
CAS: 1330-20-7
Index no: 601-022-00-9
Registration no: 01-2119488216-32-XXXX
Classification 1272/2008/EC: Flam. Liq. 3; H226; Acute Tox. 4; H332; Acute Tox. 4; H312; Skin Irrit. 2; H315.

1-Methoxy-2-propyl acetate
the substance has an occupational exposure limit(s) (PL); substance with a Community-wide occupational exposure limit value *
10-15%
EC: 203-603-9
CAS: 108-65-6
Index no: 607-195-00-7
Registration no: 01-2119475791-29-XXXX
Classification 1272/2008/EC: Flam. Liq. 3; H226.

Butylglycol acetate
the substance has an occupational exposure limit(s) (PL); substance with a Community-wide occupational exposure limit value *
1-5%
EC: 203-933-3
CAS: 112-07-2
Index no: 607-038-00-2
Registration no: 01-2119475112-47-XXXX
Classification 1272/2008/EC: Acute Tox. 4, H332; Acute Tox. 4; H312.

Note C: Some organic substances are placed on the market as a specific isomer or as a mixture of several isomers. In this case, the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers. *

Full text of hazard statements provided in section 16 of the Sheet.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures
General information: See section 11 of the Material Safety Data Sheet.

Airways: If difficulties in breathing occur, remove the victim to fresh air and keep at rest in a position comfortable for breathing.*

Skin: In case of skin contamination, immediately remove all contaminated clothing and wash contaminated skin with plenty of soap and water. Rinse skin with water/or shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation persists, consult a doctor.*

Eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call a doctor. In the case of contact with eyes, immediately rinse with plenty of water and get medical advice.*

Alimentary tract: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Immediately call a doctor.*

4.2. Most important symptoms both acute and delayed
Vapours may cause drowsiness and dizziness. Repeated exposure may cause skin dryness or cracking.

4.3. Indications of any immediate medical attention and special treatment needed
Special measures should be available in the workplace for specialist and immediate assistance.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media
Extinguishing powder, foam resistant to alcohol, carbon dioxide, water mist.
Do not use strong jets of water.

5.2. Special hazards arising from the substance or mixture
As a result of a fire, carbon monoxide and other toxic gases are generated.

5.3. Advice for fire fighters
Fire-fighting teams should wear self-contained breathing apparatus and light protective clothing. Cool adjacent tanks by spraying water from a safe distance.

ACRYLIC COAT 2:1 HS PROFESSIONAL

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency measures

For personnel non taking part in emergency procedures:

Eliminate ignition sources. Provide sufficient ventilation of the room. Avoid direct contact with the released substance. Avoid contact with skin and eyes. Personal protection measures – see section 8 of the Sheet.

For personnel taking part in emergency procedures:

Persons giving aid should wear protective clothing made of coated impregnated fabric, protective gloves (viton), tight protective glasses and breathing apparatus: gas mask with A type absorber

6.2. Environmental precautions

Prevent from penetrating into sewage system, surface water, ground water and soil.

6.3. Methods and materials for containment and cleaning up

Cover the spilled product with a non-combustible material such as sand, earth, vermiculite. Collect the product mechanically. *

6.4. Reference to other sections

Personal protection measures – see section 8 of the Sheet. Disposal considerations – see section 13 of the Sheet.

SECTION 7: HANDLING AND STORAGE OF SUBSTANCES AND MIXTURES

7.1. Precautions for safe handling

Keep away from heat and ignition sources. Prevent from penetrating into sewage system, surface water, ground water and soil. Use only in well-ventilated rooms. Do not smoke. Do not inhale vapour. Avoid contact with skin and eyes. Take precautionary measures against electrostatic discharges. Use personal protection measures – see section 8 of the Sheet.

Hygiene recommendations*:

Wash contaminated clothes before using them again. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink and smoke when using the product. Wash hands after each contact with the product.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed, original containers. Do not store near large amounts of organic peroxides or other strong oxidants. Take precautionary measures against electrostatic discharges. Store in cool and well-ventilated rooms. Protect from low temperatures, sunlight and heat sources.

7.3. Special end use (s)

For professional use in car refinishing taking into consideration the information included in subsections 7.1 and 7.2 of the Sheet.

SECTION 8 EXPOSURE CONTROL/PERSONAL PROTECTION MEASURES

8.1. Control parameters

National values of the highest permissible concentrations in the work environment and biological limit values*:

Xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m ³
IOEL STEL [ppm]	100 ppm
Warning	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Poland- The highest permissible concentration at the workplace	
Local name	Xylene mixture of isomers: 1.2-; 1.3-; 1.4-
NDS (OEL TWA)	100 mg/m ³
NDSch (OEL STEL)	200 mg/m ³
Regulatory reference	Official Journal 2018 item 1286
1-Methoxy-2-propyl acetate (108-65-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA [ppm]	50 ppm
IOEL STEL	550 mg/m ³
IOEL STEL [ppm]	100 ppm
Warning	Skin

ACRYLIC COAT 2:1 HS PROFESSIONAL

Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Poland- The highest permissible concentration at the workplace	
Local name	2-methoxy-1-methylethyl acetate
NDS (OEL TWA)	260 mg/m ³
NDSCh (OEL STEL)	520 mg/m ³
Regulatory reference	Official Journal 2018 item 1286
Butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m ³
IOEL STEL [ppm]	150 ppm
Regulatory reference	COMMISSION DIRECTIVE-EU) 2019/ 1831
Poland- The highest permissible concentration at the workplace	
Local name	n-butyl acetate
NDS (OEL TWA)	240 mg/m ³
NDSCh (OEL STEL)	720 mg/m ³
Regulatory reference	Official Journal 2018 item 1286
Butylglycol acetate (112-07-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Butoxyethyl acetate
IOEL TWA [ppm]	20 ppm
IOEL STEL	333 mg/m ³
IOEL STEL [ppm]	50 ppm
Warning	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Poland- The highest permissible concentration at the workplace	
Local name	2-butoxyethyl acetate
NDS (OEL TWA)	100 mg/m ³
NDSCh (OEL STEL)	300 mg/m ³
Regulatory reference	Official Journal 2018 item 1286

Recommended monitoring procedures*:

Monitoring method	
Monitoring method	EN 482. Exposure at workplaces- general requirements for the characteristics of chemical agents measurement procedures.

Air pollutants formation*:

No further data available.

DNEL and PNEC*:

Xylene (1330-20-7)	
DNEL/DMEL (Workers)	
Acute - systemic effects after inhalation	289 mg/m ³
Acute - local effects after inhalation	289 mg/m ³
Long-term - systemic effects, in contact with skin	180 mg/kg body weight /day
Long - term systemic effects after inhalation	77 mg/m ³
DNEL/ DMEL (General population)	
Acute - systemic effects after inhalation	174 mg/m ³
Acute - local effects after inhalation	174 mg/m ³
Long - term systemic effects after ingestion	1.6 mg/kg body weight /day
Long - term systemic effects after inhalation	14.8 mg/m ³
Long-term - systemic effects, in contact with skin	108 mg/kg body weight /day
PNEC (Water)	
PNEC (freshwater)	0.327 mg/l

ACRYLIC COAT 2:1 HS PROFESSIONAL

PNEC (sea water)	0.327 mg/l
PNEC aqua (intermittent, freshwater)	0.327 mg/l
PNEC (Sediments)	
PNEC sediments (freshwater)	12.46 mg/kg of dry mass
PNEC sediments (sea water)	12.46 mg/kg of dry mass
PNEC (Soil)	
PNEC Soil	2.31 mg/kg of dry mass
PNEC (STP)	
PNEC Sewage Treatment Plant	6.58 mg/l
1-Methoxy-2-propyl acetate (108-65-6)	
DNEL/DMEL (Workers)	
Acute - local effects after inhalation	550 mg/m ³
Long-term - systemic effects, in contact with skin	796 mg/kg body weight /day
Long - term systemic effects after inhalation	275 mg/m ³
DNEL/ DMEL (General population)	
Long - term systemic effects after ingestion	36 mg/kg body weight /day
Long - term systemic effects after inhalation	33 mg/m ³
Long-term - systemic effects, in contact with skin	320 mg/kg body weight /day
Long - term local effects after inhalation	33 mg/m ³
PNEC (Water)	
PNEC (freshwater)	0.635 mg/l
PNEC (sea water)	0.0635 mg/l
PNEC aqua (intermittent, freshwater)	6.35 mg/l
PNEC (Sediments)	
PNEC sediments (freshwater)	3.29 mg/kg of dry mass
PNEC sediments (sea water)	0.329 mg/kg of dry mass
PNEC (Soil)	
PNEC Soil	0.29 mg/kg of dry mass
PNEC (STP)	
PNEC Sewage Treatment Plant	100 mg/l
Butyl acetate (123-86-4)	
PNEC (Water)	
PNEC (freshwater)	0.18 mg/l
PNEC (sea water)	0.018 mg/l
PNEC aqua (intermittent, freshwater)	0.36 mg/l
PNEC (Sediments)	
PNEC sediments (freshwater)	0.981 mg/kg of dry mass
PNEC sediments (sea water)	0.0981 mg/kg of dry mass
PNEC (Soil)	
PNEC Soil	0.0903 mg/kg of dry mass
PNEC (STP)	
PNEC Sewage Treatment Plant	35.6 mg/l
Butylglycol acetate (112-07-2)	
DNEL/DMEL (Workers)	
Acute - systemic effects, in contact with skin	120 mg/kg body weight /day
Acute - local effects after inhalation	333 mg/m ³
Long-term - systemic effects, in contact with skin	169 mg/kg body weight /day
Long - term systemic effects after inhalation	133 mg/m ³
DNEL/ DMEL (General population)	
Acute - systemic effects, in contact with skin	72 mg/kg body weight /day
Acute - systemic effects after ingestion	36 mg/kg body weight /day

ACRYLIC COAT 2:1 HS PROFESSIONAL

Acute - local effects after inhalation	200 mg/m ³
Long - term systemic effects after ingestion	8.6 mg/kg body weight /day
Long - term systemic effects after inhalation	80 mg/m ³
Long-term - systemic effects, in contact with skin	102 mg/kg body weight /day
PNEC (Water)	
PNEC (freshwater)	0.304 mg/l
PNEC (sea water)	0.0304 mg/l
PNEC aqua (intermittent, freshwater)	0.56 mg/l
PNEC (Sediments)	
PNEC sediments (freshwater)	2.03 mg/kg of dry mass
PNEC sediments (sea water)	0.203 mg/kg of dry mass
PNEC (Soil)	
PNEC Soil	0.415 mg/kg of dry mass
PNEC (Oral)	
PNEC after ingestion (secondary poisoning)	60 mg/kg of food
PNEC (STP)	
PNEC Sewage Treatment Plant	90 mg/l

Risk management*:

No further data available.

8.2. Exposure control

Technical control measures*: Provide good ventilation of the workplace.

Symbols of personal protective equipment*:



Respiratory protection: Gas mask with A1/ B1 type absorber (EN 14387). *

Hands protection: Protective gloves PN-EN 374-3 (viton, thickness 0.7 mm, penetration time >480 min. nitrile rubber, thickness 0.4 mm, penetration time >30 min.).

Eyes protection: Tight protective glasses.

Skin protection: Proper protective clothes (coated impregnated fabrics).

Workplace: Local extractors and general ventilation.

The personal protective equipment used should meet the requirements of applicable law.

Environmental control: Prevent from penetrating into sewage system, surface water, ground water and soil.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties*

Physical state	liquid
Colour:	clear
Odour	strong, penetrating
Odour threshold	0.9-9 mg/m ³ (xylene)
Melting/freezing point	not applicable
Boiling point	120-130°C
Flammability of the materials*:	Not applicable
Explosive properties	not applicable
Explosion limits:	% bottom: 1.1 Vol %, top: 8.0 Vol% (xylene)
Flash point	26°C
Auto ignition point	app.435°C
Breakdown point	not specified
pH	not applicable.
Kinematic viscosity	not available
Solubility (in water)	poor
n-octanol/water partition coefficient (log Kow)*	not available
Vapour pressure	9 hPa (20°C)

ACRYLIC COAT 2:1 HS PROFESSIONAL

Vapour pressure at 50°C*
Density
Relative density at 20°C*
Particle characteristics*

not available
app. 1.0 g/cm³ (20°C)
not available
not applicable

9.2. Other information

No data.

SECTION 10 STABILITY AND REACTIVITY

10.1. Reactivity

The product is not reactive under normal conditions.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

As a result of thermal decomposition, carbon monoxide and other toxic gases are generated.

10.4. Conditions to be avoided

Flammable product. Avoid contact with strong oxidants, peroxides, strong acids and bases. Avoid generation and accumulation of static electricity. Protect from sunlight and heat sources.

10.5. Incompatible materials

Avoid contact with large amounts of organic peroxides, strong acids and bases, as well as other strong oxidants.

10.6. Hazardous decomposition products

As a result of thermal decomposition, carbon monoxide and other toxic gases are generated.
No hazardous decomposition product shall be formed under normal conditions of storage and use.*

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Information on the hazard classes defined in Regulation (EC) No 1272/2008*

Acute toxicity (oral): Not classified (based on available data the classification criteria are not met).
Acute toxicity (skin): Not classified (based on available data the classification criteria are not met).
Acute toxicity (inhalation): Not classified (based on available data the classification criteria are not met).

Xylene (1330-20-7)	
LD50 oral, rat	3523 mg/kg (rat)
LD50 skin, rabbit	12126 mg/kg body weight Animal: rabbit, Animal sex: male
LC50 inhalation - rat	27124 mg/l
1-Methoxy-2-propyl acetate (108-65-6)	
LD50, skin, rat	> 2000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Butyl acetate (123-86-4)	
LD50 oral, rat	12.2 ml/kg Source: ECHA
LC50 inhalation - rat (vapours)	> 4.9 mg/l Source: ECHA
Butylglycol acetate (112-07-2)	
LD50 oral, rat	≈ 1880 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute and Toxicity), Remarks on results: other:
LD50 skin, rabbit	≈ 1500 mg/kg body weight Animal: rabbit, Remarks on results: other:
LC50 Inhalation - Rat [ppm]	> 400 ppm Source: ECHA

Skin corrosion/irritation: Causes skin irritation.
pH: Not applicable.

Butyl acetate (123-86-4)	
pH	6.2 Temp.: 20 °C Concentration: 5.3 g/L

Serious eye damage/eye irritation: Not classified (based on available data the classification criteria are not met).
pH: Not applicable.

Butyl acetate (123-86-4)	
pH	6.2 Temp.: 20 °C Concentration: 5.3 g/L

Allergic effect on airways or skin: Not classified (based on available data the classification criteria are not met).
Mutagenic effect on germ cells: Not classified (based on available data the classification criteria are not met).
Carcinogenic effect: Not classified (based on available data the classification criteria are not met).

ACRYLIC COAT 2:1 HS PROFESSIONAL

Harmful effect on reproduction: Not classified (based on available data the classification criteria are not met).
 Specific target organ toxicity – single exposure: May cause drowsiness or dizziness.

Butyl acetate (123-86-4)	
Specific target organ toxicity – single exposure	May cause drowsiness or dizziness.

Specific target organ toxicity – repeated exposure: Not classified (based on available data the classification criteria are not met).

Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
1-Methoxy-2-propyl acetate (108-65-6)	
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (Skin, rat /rabbit, 90 days)	> 1000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg body weight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
Butylglycol acetate (112-07-2)	
NOAEL (Skin, rat /rabbit, 90 days)	> 150 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Aspiration hazard: Not classified (based on available data the classification criteria are not met).

Butyl acetate (123-86-4)	
Kinematic viscosity	0,83 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'

11.2. Information on other hazards*
 No further data available.

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

Hazardous for the aquatic environment, short-time (acute): Not classified (based on available data the classification criteria are not met).*
 Hazardous to the aquatic environment, long-term (chronic): Not classified (based on available data the classification criteria are not met).*
 NOT rapidly degradable.*

Xylene (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustaceans [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
NOEC for chronic toxicity to fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
1-Methoxy-2-propyl acetate (108-65-6)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustaceans [1]	> 500 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC for chronic toxicity to fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
Butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l Source: ECHA
EC50 - Crustaceans [1]	44 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	246 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

ACRYLIC COAT 2:1 HS PROFESSIONAL

Butylglycol acetate (112-07-2)	
LC50 - Fish [1]	20-40 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustaceans [1]	37 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1570 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	520 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
Algae ErC50	1570 mg/l Source: ECHA

12.2. Persistence and degradability

No further data available.*

12.3. Bioaccumulative potential

n-octanol/water partition coefficient (Log Pow):*

Butyl acetate: 1.78 Source: HSDB

Butylglycol acetate 1.51 Source: ECHA

12.4. Mobility in soil

No further data available.*

12.5 Results of PBT and vPvB assessment

No data.

12.6. Endocrine disrupting properties*

No further data available.*

12.7. Other hazardous effects*

No data.

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of according to applicable local and official waste regulations – see section 15.

Product remains:

Waste code: 08 01 11.

Do not discharge the product into the sewage system. Must not be disposed of with municipal waste. Remove the remains of the mixture carefully and harden with the use of the proper B component, a (waste) hardener from the set. Hardened product is not a hazardous waste. CAUTION: harden the remains in small portions away from flammable products. High amounts of heat are released during chemical reaction!

Contaminated packaging:

Packaging containing unhardened product remains is hazardous waste.

Waste code: 15 01 10.

Must not be disposed of with municipal waste. Contaminated container should be handed over to entities, which are authorized to collect, recover or dispose of wastes.

SECTION 14 TRANSPORT INFORMATION

14.1. UN number or ID number*

1866

14.2. UN proper shipping name*

ADR: RESIN, SOLUTION

IMDG: RESIN SOLUTION *

IATA: RESIN SOLUTION *

Description of the shipping document*:

ADR: UN 1866 RESIN, SOLUTION, 3, III, (D/E)

IMDG: UN 1866 RESIN SOLUTION, 3, III (26°C c.c.)

IATA: UN 1866 Resin solution, 3, III

14.3. Transport hazard class (-es)

3



14.4. Packaging group

III

ACRYLIC COAT 2:1 HS PROFESSIONAL

14.5. Environmental hazards

Environmentally hazardous: No. *
Marine pollutants: No. *

14.6. Special precautions for users

Road transport*:

Classification code (ADR): F1
Limited Quantities (ADR): 5 L
Special packing provisions (ADR): PP1
Mixed Packing Regulations (ADR): MP19
Transport category (ADR): 3



Orange Tiles:

Tunnel restriction code (ADR): D/E

Sea transport*:

Special provisions (IMDG): 223, 955
Limited Quantities (IMDG): 5 L
Special packing provisions (IMDG): PP1
EmS number (Fire): F-E
EmS number (Spillage): S-E
Cargo Stowage Category (IMDG): A

Air transport*:

No data.

14.7. Sea transport in bulk in accordance with IMO instruments*

Not applicable.

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations / legislations specific for the substance or mixture

EU Provisions*:

Annex XVII to the REACH Regulation (restriction conditions): It does not contain substances listed in Annex XVII to the REACH Regulation (restriction conditions).

Annex XIV to the REACH Regulation (List of Authorizations): It does not contain substances listed in Annex XIV to the REACH Regulation (List of Authorizations).

REACH Candidate List (SVHC): Contains no substances listed on the REACH Candidate List.

PIC Regulation (EU 649/2012, Prior Informed Consent): It does not contain substances listed on the PIC list (EU Regulation 649/2012 on the export and import of dangerous chemicals).

POP Regulation (EU 2019/1021, Persistent Organic Pollutants): It does not contain substances listed on the POP list (EU Regulation 2019/1021 on the export and import of dangerous chemicals).

Ozone Depletion Regulation (EU 1005/2009): Contains no substances listed in the ozone depleting list (EU Regulation 1005/2009 on substances that deplete the ozone layer).

Explosives Precursors Regulation (EU 2019/1148): It does not contain substances listed on the list of explosives precursors (EU Regulation 2019/1148 on the marketing and use of explosives precursors).

Drug Precursors Regulation (EC 273/2004): It does not contain any substance(s) listed on the list of drug precursors (Regulation EC 273/2004 on the manufacture and marketing of certain substances used for the illicit manufacture of narcotic drugs and psychotropic substances).

Other regulations*:

Material Safety Data Sheet EU format according to Commission Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

ADR Agreement: Government Statement of February 18, 2021 on the entry into force of amendments to Annexes A and B of the European Agreement on the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957. (Journal of Laws of 2019, , item 874).

15.2 Chemical safety assessment

Not performed.

SECTION 16 OTHER INFORMATION

Full text of hazard statements H phrases mentioned in section 2 - 15 of the Sheet:

Flam. Liq. 3 Flammable liquids, cat. 3.
H226 Flammable liquid and vapour.

ACRYLIC COAT 2:1 HS PROFESSIONAL

STOT SE 3	Specific target organ toxicity – single exposure, cat. 3.
H336	May cause drowsiness or dizziness.
Acute Tox. 4	Acute toxicity, cat. 4.
H332	Harmful if inhaled.
H312	Harmful in contact with skin.
Skin Irrit. 2	Skin corrosion/irritation, cat. 2
H315	Causes skin irritation, cat. 2,
EUH066	Repeated exposure may cause skin dryness or cracking.

Explanation of abbreviations and acronyms used in the MSDS:

CAS no	numerical symbol ascribed to a chemical substance by the American organization Chemical Abstracts Service (CAS).
EC no	a number ascribed to a chemical substance in the European List of Existing Chemical Substances (EINECS), or a number in the European Inventory of Notified Chemical Substances, mentioned in "No-longer polymers" publication (EINECS) or a number on the list of chemicals listed in 'No-longer polymers'.
MPC	maximum permissible concentration of health hazardous substances in the work place
MPIC	Maximum Permissible Instantaneous Concentration.
NDSP	Maximum Permissible Ceiling Concentration.
PBC	Permissible concentration in biological material
UN number	four-digit identification number of a substance, preparation or product pursuant to UN model regulations

Classification was made using the calculation method in accordance with the classification rules contained in Regulation No. 1272/2008 / EC

Other data sources:

ECHA European Chemicals Agency
TOXNET Toxicology Data Network

Changes in the Sheet compared to the previous version:

Update of sections:

9: rewording of sub-section 9.1: Information on basic physical and chemical properties

11: rewording of sub-section 11.1: Information on the hazard classes defined in Regulation (EC) No 1272/ 2008: added subsection 11.2.

Information on other hazards

12: new subsection 12.6: Endocrine disrupting properties.

14: rewording of sub-section 14.1: UN number or ID number; rewording of sub-section 14.7: Sea transport in bulk in accordance with IMO instruments.

Changes in the content of sections: 2.3, 3.2, 4.1, 5.1, 6.3, 7.1, 8.1, 8.2, 9.1, 10.6, 11.1, 11.2, 12.1, 12.2, 12.3, 12.4, 12.6, 12.7, 14.1, 14.2, 14.5, 14.6, 14.7, 15.1, 16.

General update.

Sheet number: 00-0P1L-0123-V7