

ACRYLIC PPRIMER S-2000 5:1**SECTION 1: SUBSTANCE/MIXTURE IDENTIFICATION AND MANUFACTURER/SUPPLIER IDENTIFICATION****1.1. Product identification***

Product form: Mixtures
Name: Acrylic primer
Trade name: S-2000
UFI Code:
7VR0-N0U7-600X-Q3RF PRIMER S-2000GREY
DYR0-50HM-H00E-DFAH PRIMER S-2000BLACK
D2S0-P070-T00W-1SWK PRIMER S-2000WHITE
44S0-50WE-400E-Q4GN PRIMER S-2000RED
07S0-P0KT-E00W-CG2Q PRIMER S-2000GRAPHITE
DAS0-6096-R00D-1TNS PRIMER S-2000YELLOW

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses
For professional use in car refinish.

1.2.2. Uses advised against
No further data available. *

1.3 Data of the safety data sheet supplier**Przedsiębiorstwo RANAL Sp. z o.o.**

Ul. Łódzka 3
42-240 Rudniki k. Częstochowy, PL

Tel.: +48 34 329 45 03
Fax: +48 34 320 12 16
Registration number 000029202

Person responsible for the safety data sheet: ranal@ranal.pl

1.4. Emergency telephone

+48 34 329 45 03 (8.00 - 15.00)

SECTION 2: HAZARDS IDENTIFICATION**2.1. Classification of the substance or mixture**

Classification according to the regulation (EC) no 1272/2008 [CLP].
Flammable liquids, cat. 3, H226
Skin corrosion/irritation, cat. 2, H315

Full text of H and EUH phrases: see section 16.

Adverse effects related to physicochemical properties, effects on human health and the environment:
No further data available.

2.2 Label elements

Labelling according to the regulation (EC) no 1272/2008 [CLP]:

Hazard pictograms (CLP):



GHS02 GHS07

Signal word (CLP): **Warning.**

Contains: Xylene

Hazard statements (CLP):

H226 Flammable liquid and vapour.
H315 Causes skin irritation.

Precautionary statements (CLP):

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Do not breathe vapours, spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.

EUH phrases:

EUH211 Warning! Hazardous respirable droplets may form if sprayed. Do not breathe spray or vapour. *

2.3 Other hazards

Does not contain PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with Annex XIII of REACH. *

ACRYLIC PPRIMER S-2000 5:1

The mixture does not contain any substance(s) included in the list established in accordance with Art. 59 sec. 1 of the REACH Regulation due to endocrine disrupting properties or is not identified as endocrine disrupting in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in a concentration equal to or greater than 0,1 % by weight. *

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS
3.1. Substances

Not applicable.

3.2. Mixtures

*

Name	Product identification	%	Classification according to the regulation (EC) no 1272/2008[CLP]
Xylene the substance has an occupational exposure limit(s) (PL); substance with a Community-wide occupational exposure limit value * (Note C)*	CAS number: 1330-20-7 EC number: 215-535-7 Index number: 601-022-00-9 REACH: 01-2119488216-32	5 – 15*	Flam. Liq. 3, H226 Acute Tox. 4(Skin), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
Titanium dioxide ;[as a powder with 1% or more of particles with an aerodynamic diameter of ≤10 µm]* the substance has an occupational exposure limit(s) (PL)* (Note V)(Note W)(Note 10)	CAS number: 13463-67-7 EC number: 236-675-5 Index number: 022-006-00-2 REACH: 01-2119489379-17	< 13	Carc. 2, H351
1-Methoxy-2-propyl acetate the substance has an occupational exposure limit(s) (PL); substance with a Community-wide occupational exposure limit value *	CAS number: 108-65-6 EC number: 203-603-9 Index number: 607-195-00-7 REACH: 01-2119475791-29	5 – 10*	Flam. Liq. 3, H226
Butyl acetate the substance has an occupational exposure limit(s) (PL); substance with a Community-wide occupational exposure limit value *	CAS number: 123-86-4 EC number: 204-658-1 Index number: 607-025-00-1 REACH: 01-2119485493-29	5 – 10*	Flam. Liq. 3, H226 STOT SE 3, H336

Note 10: The classification as an inhalation carcinogen applies only to mixtures in the form of a powder containing 1 % or more of titanium dioxide in the form of particles with an aerodynamic diameter of ≤ 10 µm or incorporated in such particles. *

Note C: Some organic substances are placed on the market as a specific isomer or as a mixture of several isomers. In this case, the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers. *

Note V: If the substance is to be placed on the market as fibers (diameter < 3 µm, length > 5 µm, aspect ratio ≥ 3:1) or as particles of the substance meeting the WHO criteria for fibers or as particles with modified surface chemistry, their hazardous properties should be assessed in accordance with Title II of this Regulation to assess whether a higher category should be applied (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal). *

Note W: A carcinogenic risk associated with this substance has been observed to occur when respirable dust is inhaled in amounts that severely impair the natural mechanisms for clearing particles from the lungs. This note is a description of the specific type of toxicity of the substance, not a criterion for classification under this Regulation. *

Full text of H and EUH phrases: see section 16. *

SECTION 4: FIRST AID MEASURES
4.1. Description of first aid measures

First aid – general measures:

General information: See section 11 of the Material Safety Data Sheet.

First aid – after inhalation: If difficulties in breathing occur, remove the victim to fresh air and keep at rest in a position comfortable for breathing. *

First aid – after skin contact: In the event of skin contamination take off contaminated clothing. Wash contaminated skin with plenty of water and soap. Rinse skin with water/or shower. If skin irritation or rash occurs: get medical advice/attention. If skin irritation persists, consult a doctor. *

First aid – after contact with eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call a doctor. In the case of contact with eyes, immediately rinse with plenty of water and get medical advice. *

First aid – after ingestion: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Immediately call a doctor. *

4.2 Most important symptoms both acute and delayed

Symptoms/effects in the event of inhalation: Vapours may cause drowsiness and dizziness.

Symptoms/effects in the event of skin contact: Prolonged or repeated contact may cause skin dryness. *

Symptoms/effects in the event of contact with eyes: May cause eye irritation. *

4.3 Indications of any immediate medical attention and special treatment needed

Symptomatic treatment. *

ACRYLIC PPRIMER S-2000 5:1

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing agents: Extinguishing powder, foam resistant to alcohol, carbon dioxide, water mist.

Unsuitable extinguishing media: do not use a strong stream of water. *

5.2 Special hazards arising from the substance or mixture

As a result of a fire, carbon monoxide and other toxic gases are generated.

5.3. Advice for fire fighters

Protection during firefighting: Do not intervene without appropriate protective equipment. Self-contained, breathing apparatus. Complete protective clothing. *

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency measures

6.1.1. For personnel non taking part in emergency procedures

Eliminate ignition sources. Provide sufficient ventilation of the room. Avoid any direct and indirect contact with released components*.

Avoid contact with skin and eyes. Use the required personal protection measures – see section 8 of the Sheet.

6.1.2. For personnel taking part in emergency procedures

Do not intervene without appropriate protective equipment. See section 8. *

6.2 Environmental precautions

Avoid release to the environment. Prevent from entering surface water and sewage system. Do not allow the product to enter groundwater, water reservoirs or sewage systems, even in small quantities. *

6.3 Methods and materials for containment and cleaning up

Preventing the spread of contamination: Cover the spilled product with a non-combustible material such as sand, earth, vermiculite. Collect the product mechanically. *

6.4 Reference to other sections

Personal protection measures – see section 8 of the Sheet. Disposal considerations – see section 13 of the Sheet.

SECTION 7: HANDLING AND STORAGE OF SUBSTANCES AND MIXTURES

7.1. Precautions for safe handling

Precautions for safe handling: Provide good ventilation of the workplace. Keep away from heat sources, hot surfaces, sources of sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear personal protection measures. *

Hygiene recommendations: Wash contaminated clothes before using them again. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink and smoke when using the product. Wash hands after each contact with the product. *

7.2 Conditions for safe storage, including any incompatibilities

Technical measures: Ground/bond container and receiving equipment. *

Storage conditions: Store in a well-ventilated place. Keep cool. Keep container tightly closed. *

7.3 Special end use (s)

No further data available. *

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION MEASURES

8.1. Control parameters

8.1.1. National values of the highest permissible concentrations in the work environment and biological limit values*

Xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Xylene, mixed isomers, pure
IOEL TWA [ppm]	50 ppm
IOEL STEL	442 mg/m ³
IOEL STEL [ppm]	100 ppm
Warning	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Poland- The highest permissible concentration at the workplace	
Local name	Xylene mixture of isomers: 1,2-; 1,3-; 1,4-
NDS (OEL TWA)	100 mg/m ³
NDSch (OEL STEL)	200 mg/m ³
Regulatory reference	Official Journal 2018 item 1286
1-Methoxy-2-propyl acetate (108-65- 6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA [ppm]	50 ppm
IOEL STEL	550 mg/m ³
IOEL STEL [ppm]	100 ppm
Warning	Skin

MATERIAL SAFETY DATA SHEET

Material Safety Data Sheet EU format according to Commission Regulation (EU) 2020/878

Issue date: 4.05.2012, updating date: 18.01.2023, version: 5

ACRYLIC PPRIMER S-2000 5:1

Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Poland- The highest permissible concentration at the workplace	
Local name	2-methoxy-1-methylethyl acetate
NDS (OEL TWA)	260 mg/m ³
NDSch (OEL STEL)	520 mg/m ³
Regulatory reference	Official Journal 2018 item 1286

Butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m ³
IOEL STEL [ppm]	150 ppm
Regulatory reference	COMMISSION DIRECTIVE-EU) 2019/ 1831
Poland- The highest permissible concentration at the workplace	
Local name	n-butyl acetate
NDS (OEL TWA)	240 mg/m ³
NDSch (OEL STEL)	720 mg/m ³
Regulatory reference	Official Journal 2018 item 1286

Titanium dioxide; [as a powder with 1% or more of particles with an aerodynamic diameter of ≤10 µm](13463-67-7)	
Poland- The highest permissible concentration at the workplace	
Local name	Titanium dioxide
NDS (OEL TWA)	10 mg/ m ³ inhalable fraction
Warning	Inhalable fraction - fraction of the aerosol penetrating through the nose and mouth, which, when deposited in the respiratory tract, poses a health risk. Simultaneous determination of concentrations of the respirable crystalline silica fraction is mandatory.
Regulatory reference	Official Journal 2018 item 1286

8.1.2. Recommended monitoring procedures*

Monitoring method: EN 482. Exposure at workplaces- general requirements for the characteristics of chemical agents measurement procedures.

8.1.3. Air pollutants are formed*

No further data available.

8.1.4. DNEL and PNEC*

Xylene (1330-20-7)	
DNEL/DMEL (Workers)	
Acute - systemic effects after inhalation	289 mg/m ³
Acute - local effects after inhalation	289 mg/m ³
Long-term - systemic effects, in contact with skin	180 mg/kg body weight /day
Long - term systemic effects after inhalation	77 mg/m ³
DNEL/ DMEL (General population)	
Acute - systemic effects after inhalation	174 mg/m ³
Acute - local effects after inhalation	174 mg/m ³
Long - term systemic effects after ingestion	1.6 mg/kg body weight /day
Long - term systemic effects after inhalation	14.8 mg/m ³
Long-term - systemic effects, in contact with skin	108 mg/kg body weight /day
PNEC (Water)	
PNEC (freshwater)	0.327 mg/l
PNEC (sea water)	0.327 mg/l
PNEC aqua (intermittent, freshwater)	0.327 mg/l
PNEC (Sediments)	
PNEC sediments (freshwater)	12.46 mg/kg of dry mass
PNEC sediments (sea water)	12.46 mg/kg of dry mass
PNEC (Soil)	
PNEC Soil	2.31 mg/kg of dry mass
PNEC (STP)	
PNEC Sewage Treatment Plant	6.58 mg/l

1-Methoxy-2-propyl acetate (108-65-6)	
DNEL/DMEL (Workers)	
Acute - local effects after inhalation	550 mg/m ³
Long-term - systemic effects, in contact with skin	796 mg/kg body weight /day
Long - term systemic effects after inhalation	275 mg/m ³
DNEL/ DMEL (General population)	
Long - term systemic effects after ingestion	36 mg/kg body weight /day
Long - term systemic effects after inhalation	33 mg/m ³
Long-term - systemic effects, in contact with skin	320 mg/kg body weight /day
Long - term local effects after inhalation	33 mg/m ³
PNEC (Water)	
PNEC (freshwater)	0.635 mg/l
PNEC (sea water)	0.0635 mg/l
PNEC aqua (intermittent, freshwater)	6.35 mg/l
PNEC (Sediments)	
PNEC sediments (freshwater)	3.29 mg/kg of dry mass
PNEC sediments (sea water)	0.329 mg/kg of dry mass
PNEC (Soil)	
PNEC Soil	0.29 mg/kg of dry mass
PNEC (STP)	
PNEC Sewage Treatment Plant	100 mg/l

MATERIAL SAFETY DATA SHEET

Material Safety Data Sheet EU format according to Commission Regulation (EU) 2020/878

Issue date: 4.05.2012, updating date: 18.01.2023, version: 5

ACRYLIC PPRIMER S-2000 5:1**Butyl acetate (123-86-4)****PNEC (Water)**

PNEC (freshwater)	0.18 mg/l
PNEC (sea water)	0.018 mg/l
PNEC aqua (intermittent, freshwater)	0.36 mg/l

PNEC (Sediments)

PNEC sediments (freshwater)	0.981 mg/kg of dry mass
PNEC sediments (sea water)	0.0981 mg/kg of dry mass

PNEC (Soil)

PNEC Soil	0.0903 mg/kg of dry mass
-----------	--------------------------

PNEC (STP)

PNEC Sewage Treatment Plant	35.6 mg/l
-----------------------------	-----------

8.1.5. Risk management

No further data available. *

8.2 Exposure control

8.2.1. Technical control measures*

Technical control measures:

Provide good ventilation of the workplace.

8.2.2. Personal protective equipment*

Symbols of personal protective equipment*:



8.2.2.1. Eye or face protection*

Eyes protection:

Safety glasses *

8.2.2.2. Skin protection*

Skin and body protection:

Wear suitable protective clothes. *

Hands protection:

Protective gloves. *

Hand protection

Type	Material	Breakthrough time	Thickness (mm)	Penetration	Standards
Disposable gloves	Viton® II	6 (> 480 minutes)	0.7 mm		EN 374-3
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	0.4 mm		EN 374-3

8.2.2.3. Respiratory protection*:

Respiratory protection:

In case of insufficient ventilation, wear suitable breathing apparatus. *

Respiratory protection

Equipment	Filter type	Condition	Standard
Gas mask with filter type	Filter A1/B1		EN 14387

8.2.2.4. Thermal hazards

No further data available. *

8.2.3. Environmental control*

Environmental control

Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****Physical state**

liquid

Colour

according to specification

Odour

strong, penetrating

Odour threshold0.9-9.0 mg/m³ (xylene)**pH**

not available*

ACRYLIC PPRIMER S-2000 5:1

Melting point	not applicable
Freezing point	* not available*
Boiling point	126-145°C
Flammability (solid, gas)	not applicable
Explosive properties	no data*
Explosion limits:	% bottom: 1.1 Vol %, top: 8.0 Vol% (xylene)
Flash point	24°C
Auto ignition point	app.270-300°C
Breakdown point	not specified
Kinematic viscosity*	5000 mm ² /s *
Solubility (in water)	poor
n-octanol/water partition coefficient:	not available*
Vapour pressure	13 hPa (20°C) (butyl acetate)
Vapour pressure at 50 °C*	not available*
Density	approx. 1.6 g/cm ³ (20°C)*
Relative density*	not available*
Relative vapour density at 20°C	* not available*
Particle characteristics*	not applicable*

9.2 Other information

9.2.1. Information with regard to physical hazard classes*

No further data available.

9.2.2. Other safety features*

No further data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

The product is not reactive under normal conditions.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions under normal conditions of use unknown. *

10.4 Conditions to be avoided

Flammable product. Avoid contact with strong oxidants, peroxides, strong acids and bases. Avoid generation and accumulation of static electricity. Protect from sunlight and heat sources.

10.5. Incompatible materials

Avoid contact with large amounts of organic peroxides, strong acids and bases, as well as other strong oxidants.

10.6. Hazardous decomposition products

No hazardous product shall be formed under normal conditions of storage and use. Thermal decomposition may produce: Carbon monoxide. Other toxic gases. *

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on the hazard classes defined in Regulation (EC) No 1272/2008*

Acute toxicity (oral): Not classified (based on available data the classification criteria are not met)

Acute toxicity (skin): Not classified (based on available data the classification criteria are not met)

Acute toxicity (inhalation): Not classified (based on available data the classification criteria are not met)

Xylene (1330-20-7)	
LD50 oral, rat	3523 mg/kg (rat)
LD50 skin, rabbit	12126 mg/kg body weight Animal: rabbit, Animal sex: male
LC50 inhalation - rat	27124 mg/l

1-Methoxy-2-propyl acetate (108-65-6)	
LD50, skin, rat	> 2000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Butyl acetate (123-86-4)	
LD50 oral, rat	12.2 ml/kg Source: ECHA
LC50 inhalation - rat (vapours)	> 4.9 mg/l Source: ECHA

Titanium dioxide; [as a powder with 1% or more of particles with an aerodynamic diameter of ≤10 µm](13463-67-7)	
LC50 inhalation - rat (dust/mist)	> 6.82 mg/l Source: ECHA

Skin corrosion/irritation: Causes skin irritation.

Butyl acetate (123-86-4)	
pH	6.2 Temp.: 20 °C Concentration: 5.3 g/L

Titanium dioxide; [as a powder with 1% or more of particles with an aerodynamic diameter of ≤10 µm](13463-67-7)	
pH	7 Source: ECHA

MATERIAL SAFETY DATA SHEET

Material Safety Data Sheet EU format according to Commission Regulation (EU) 2020/878

Issue date: 4.05.2012, updating date: 18.01.2023, version: 5

ACRYLIC PPRIMER S-2000 5:1

Serious eye damage/eye irritation: Not classified (based on available data the classification criteria are not met).

Butyl acetate (123-86-4)	
pH	6.2 Temp.: 20 °C Concentration: 5.3 g/L

Titanium dioxide; [as a powder with 1% or more of particles with an aerodynamic diameter of ≤10 µm](13463-67-7)	
pH	7 Source: ECHA

Allergic effect on airways or skin: Not classified (based on available data the classification criteria are not met).

Mutagenic effect on germ cells: Not classified (based on available data the classification criteria are not met).

Carcinogenic effect: Not classified (based on available data the classification criteria are not met).

Titanium dioxide; [as a powder with 1% or more of particles with an aerodynamic diameter of ≤10 µm](13463-67-7)	
IARC Group	2B - May be carcinogenic to humans

Harmful effect on reproduction: Not classified (based on available data the classification criteria are not met).

Specific target organ toxicity – single exposure: Not classified (based on available data the classification criteria are not met).

Butyl acetate (123-86-4)	
Specific target organ toxicity – single exposure:	May cause drowsiness or dizziness.

Specific target organ toxicity – repeated exposure: Not classified (based on available data the classification criteria are not met).

Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)

1-Methoxy-2-propyl acetate (108-65-6)	
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (Skin, rat /rabbit, 90 days)	> 1000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg body weight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	125 mg/kg body weight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)

Aspiration hazard: Not classified (based on available data the classification criteria are not met).

The mixture Acrylic Primer S-2000	
Kinematic viscosity	5000 mm ² /s

Butyl acetate (123-86-4)	
Kinematic viscosity	0.83 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'

11.2 Information on other hazards

No further data available. *

SECTION 12: ECOLOGICAL INFORMATION**12.1. Toxicity**

Hazardous for the aquatic environment, short-time (acute): Not classified (based on available data the classification criteria are not met). *

Hazardous to the aquatic environment, long-term (chronic): Not classified (based on available data the classification criteria are not met). *

It is not easily degradable. *

Xylene (1330-20-7)*	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustaceans [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
NOEC for chronic toxicity to fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

1-Methoxy-2-propyl acetate (108-65-6)*	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustaceans [1]	> 500 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC for chronic toxicity to fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

Butyl acetate (123-86-4)*	
LC50 - Fish [1]	18 mg/l Source: ECHA
EC50 - Crustaceans [1]	44 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodemus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	246 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

MATERIAL SAFETY DATA SHEET

Material Safety Data Sheet EU format according to Commission Regulation (EU) 2020/878

Issue date: 4.05.2012, updating date: 18.01.2023, version: 5

ACRYLIC PPRIMER S-2000 5:1

NOEC (chronic)	23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Titanium dioxide; [as a powder with 1% or more of particles with an aerodynamic diameter of $\leq 10 \mu\text{m}$](13463-67-7)*	
LC50 - Fish [1]	> 100 mg/l
EC50 72h - Algae [1]	> 50 mg/l Source: ECHA

12.2 Persistence and degradability

No further data available. *

12.3 Bioaccumulative potential

Butyl acetate (123-86-4)*	
n-octanol/water partition coefficient (Log Pow):	1.78 Source: HSDB

12.4 Mobility in soil

No further data available.

12.5 Results of PBT and vPvB assessment

No further data available.

12.6 Endocrine disrupting properties

No further data available.

12.7 Other hazardous effects

No further data available.

SECTION 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods**

Local regulations (waste): Dispose of according to applicable regulations. *

Waste treatment methods: Dispose of the contents/container as directed by an authorized sorting and collection center. *

Waste water disposal recommendations: Do not discharge the product into the sewage system. *

Product/packaging disposal recommendations: Dispose of the product and packaging as hazardous waste. Do not dispose of with household waste. After cleaning, recycle or dispose of at an authorized facility. *

Additional information: Flammable vapours may accumulate in the container. *




European Waste Catalogue code*:

08 01 11 * Waste paints and varnishes containing organic solvents or other dangerous substances.

15 01 10* Packaging containing residues of or contaminated by dangerous substances (e.g. pesticides of I and II class of toxicity- very toxic and toxic)*

SECTION 14: TRANSPORT INFORMATION

According to ADR/ IMDG/ IATA:

ADR	IMDG	IATA
14.1 UN number or ID number		
UN1263	UN1263	UN1263
14.2. UN proper shipping name*		
PAINT	PAINT	PAINT
Description of the shipping document		
UN 1263 PAINT, 3, III, (D/E)	UN 1263 PAINT, 3, III (24°C c.c.)	UN 1263 Paint, 3, III
14.3 Transport hazard class (-es)		
3	3	3
		
14.4. Packaging group		
III	III	III
14.5. Environmental hazards*		
Environmentally hazardous: No	Environmentally hazardous: No Marine pollutants: No	Environmentally hazardous: No
No further data available.		

ACRYLIC PPRIMER S-2000 5:1**14.6 Special precautions for users*****Road transport**

Classification code (ADR):	F1
Limited Quantities (ADR):	5 L
Special packing provisions (ADR):	PP1
Mixed Packing Regulations (ADR):	MP19
Transport category (ADR):	3
Special provisions for carriage – Packages:	V12

30**1263**

Orange Tiles:	
Tunnel restriction code (ADR):	D/E

Sea transport

Special provisions (IMDG):	163, 223, 367, 955
Limited Quantities (IMDG):	5 L
Special packing provisions (IMDG):	PP1
EmS number (Fire):	F-E
EmS number (Spillage):	S-E
Cargo Stowage Category (IMDG):	A

Air transport

No data.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 Convention and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations / legislations specific for the substance or mixture**

15.1.1. EU Provisions*

Annex XVII to the REACH Regulation (restriction conditions): It does not contain substances listed in Annex XVII to the REACH Regulation (restriction conditions).

Annex XIV to the REACH Regulation (List of Authorizations): It does not contain substances listed in Annex XIV to the REACH Regulation (List of Authorizations).

REACH Candidate List (SVHC): Contains no substances listed on the REACH Candidate List.

PIC Regulation (EU 649/2012, Prior Informed Consent): It does not contain substances listed on the PIC list (EU Regulation 649/2012 on the export and import of dangerous chemicals).

POP Regulation (EU 2019/1021, Persistent Organic Pollutants): It does not contain substances listed on the POP list (EU Regulation 2019/1021 on the export and import of dangerous chemicals).

Ozone Depletion Regulation (EU 1005/2009): Contains no substances listed in the ozone depleting list (EU Regulation 1005/2009 on substances that deplete the ozone layer).

Explosives Precursors Regulation (EU 2019/1148): It does not contain substances listed on the list of explosives precursors (EU Regulation 2019/1148 on the marketing and use of explosives precursors).

Drug Precursors Regulation (EC 273/2004):

It does not contain any substance(s) listed on the list of drug precursors (Regulation EC 273/2004 on the manufacture and marketing of certain substances used for the illicit manufacture of narcotic drugs and psychotropic substances).

15.1.2. Other regulations:*

Poland:

- Material Safety Data Sheet EU format according to Commission Regulation (EU) 2020/878.
- Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC
- Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006
- ADR Agreement: Government Statement of February 18, 2021 on the entry into force of amendments to Annexes A and B of the European Agreement on the International Carriage of Dangerous Goods by Road (ADR), drawn up in Geneva on September 30, 1957. (Journal of Laws of 2019, , item 874).

15.2 Chemical safety assessment

Not performed.

ACRYLIC PPRIMER S-2000 5:1**SECTION 16: OTHER INFORMATION**

Changes: Material Safety Data Sheet EU format according to Commission Regulation (EU) 2020/878.

Explanation of abbreviations and acronyms:

ADN European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways. *

ADREuropean Agreement concerning the International Carriage of Dangerous Goods by Road. *

ATE Estimated acute toxicity*

BCF BCF bioconcentration factor*

BLV Quantitative limit value*

BOD Biochemical Oxygen Demand (BOD)*

COD Chemical oxygen demand (COD)*

DMEL Derived level causing minimal changes*

DNEL Derived no effect level*

EC no a number ascribed to a chemical substance in the European List of Existing Chemical Substances (EINECS), or a number in the European Inventory of Notified Chemical Substances, mentioned in "No-longer polymers" publication (EINECS) or a number on the list of chemicals listed in 'No-longer polymers'.

EC50 Medium effective concentration*

ENEuropean standard*

IARC International Agency for Research on Cancer*

IATA International Air Transport Association*

IMDG International Maritime Code for Dangerous Goods*

LC50 The concentration of the substance causing the death of 50% of the population of test organisms*

LD50 The Dose causing the death of 50% of the population of test organisms*

LOAEL The lowest level at which harmful changes are observed*

NOAEC Concentration at which no adverse effects are observed*

NOAEL Dose level at which no adverse effects are observed*

NOEC Maximum Concentration at which no adverse effects are observed*

OECD Organization for Economic Cooperation and Development*

OEL Occupational exposure limit value*

PBT substance, which is Persistent, Bio-accumulative and toxic*

PNEC Predicted no-effect concentration*

RID Regulations Concerning the International Transport of Dangerous Goods by Rail.

SDS Material Safety Data Sheet

STP sewage treatment plant*

ThOD Theoretical Oxygen Demand (ThOD)*

TLM Middle tolerance limit*

LZO Volatile Organic Compounds*

N.O.S. Not otherwise specified*

vPvB very Persistent and very Bio-accumulative*

ED Endocrine disrupting properties*

CAS no numerical symbol ascribed to a chemical substance by the American organization Chemical Abstracts Service (CAS).

MPC- maximum permissible concentration of health hazardous substances in the work place

MPIC Maximum Permissible Instantaneous Concentration.

NDSP Maximum Permissible Ceiling Concentration.

PBC Permissible concentration in biological material

UN number - four-digit identification number of a substance, preparation or product pursuant to UN model regulations

Data sources: ECHA (European Chemicals Agency).

Directions for training: Use in accordance with health and safety rules and safety procedures.

Full text of hazard statements mentioned in section 2 - 15 of the Sheet:

Acute Tox. 4(Skin) Acute toxicity - (skin), cat. 4

Acute Tox. (Inhalation) Acute toxicity (after inhalation), cat. 4

Carc. 2 Carcinogenicity, Category 2

EUH211 Warning! Hazardous respirable droplets may form if sprayed. Do not breathe spray or vapour.

Flam. Liq. 3 Flammable liquid, category 3

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

Skin Irrit. 2 Skin corrosion/irritation, Category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3, narcotic effect

Classification and procedure used to determine the classification of mixtures according to the Regulation (EC) 1272/2008[CLP]

Flam. Liq. 3 H226 Based on research results

Skin Irrit. 2 H315 Calculation method

The information provided is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. Therefore, they should not be understood as a guarantee of any specific product properties.

Other data sources:

ECHA European Chemicals Agency

TOXNET Toxicology Data Network

ACRYLIC PPRIMER S-2000 5:1

Changes in the Sheet:

Update of sections:

1: added subsections 1.2.1., 1.2.2.,

6: added subsections 6.1.1., 6.1.2.,

8: added subsections 8.1.1., 8.1.2., 8.1.3., 8.1.4., 8.1.5., 8.2.1., 8.2.2. (and other subsections), 8.2.3.

9: added subsections 9.2.1., 9.2.2.,

11: rewording of sub-section 11.1: Information on the hazard classes defined in Regulation (EC) No 1272/2008

12: new subsection 12.6: Endocrine disrupting properties.

14: rewording of sub-section 14.7: Sea transport in bulk in accordance with IMO instruments.

15: added subsections 15.1.1, 15.1.2.

Changes in the content of sections:

1.1, 2.1, 2.2, 2.3, 3.2, 4.1, 4.2, 4.3, 5.1, 5.3, 6.1, 6.2, 6.3, 7.1, 7.2, 7.3, 8.1, 8.2, 9.1, 9.2, 10.3, 10.6, 11.1, 11.2, 12.1, 12.2, 12.3, 12.6, 12.7, 13.1, 14.2, 14.5, 14.6, 14.7, 15.1, 16.

General update.

Sheet number: 02-0P1L-0123-V5